



TECHNICAL PARAMETERS			CONFIGURATION		OPTIONAL
Name		Data	Name	Manufacturer	
Basic	Operating weight	21100 kg	Engine	Weichai	Work warning light
	Boom length	5675 mm	Main valve	Lonking	Walking alarm
	Arm length	2920 mm	Main pump	Lonking	MP3
	Standard bucket	0.9 m³	Swing motor	Lonking	Top protecting net
	Max.Travel speed	3.2/5.1 km/h	Travel motor	Lonking	Front protecting net
	Max.Swing speed	10.6 rpm	Electric system	Parker	600mm triple grouser shoes
	Grade ability	35°(70%)			700mm triple grouser shoes
	Ground pressure	47 kPa			Track rubber block
	Max.Traction force	208 kN			
Engine	Engine model	WP6G175E301	<div>PRODUCT FEATURES</div> <div>Weichai turbocharged common rail engine. Stable & Reliable. Fuel efficient.</div> <div>Three-stage Air & Fuel Filtering System</div> <div>Charge Air Cooling System with Parallel Radiator</div> <div>Advanced Control System with Function of Interflow & Re-activation, Swing Priority</div> <div>8 inch LCD Display with Multi Purpose</div> <div>Comfortable ROPS Cabin with 2.7m³ Operational Space</div> <div>No Frame Cab Glasses to Enlarge Operation Field of View</div> <div>Heavy-duty Working Device with High Strength Low Alloyed Steels</div> <div>Breaker Piping Kit</div>		
	Rated power	129 kW/2000 rpm			
	Max.Torque	760/1400-1500 N.m/rpm			
	Displacement	6.75 L			
	Fuel tank	400 L			
Hydraulic	Max.Flow(total)	221×2 L/min			
	Max.Working pressure	35 MPa			
	Max.Pilot pressure	4 Mpa			
	Max.Arm digging force	100 kN(ISO)			
	Max.Bucket digging force	133 kN(ISO)			
	Hrdraulic oil tank	165/256 L			
Chassis	Track width	800 mm			
	Track shoes number	46(each side)			
	Carrier rollers number	2(each side)			
	Track rollers number	7(each side)			
Electric	System vottage	24 V			
	Battery capacity	24 V,120 Ah×2			

Lonking

CDM6205
HYDRAULIC EXCAVATOR
 Efficiency Rules the Future



The following blank can be used for notes or comments.

For more information on Lonking products,
Please contact our local agent:

Lonking, Lonking CDM Series and their respective logos, as well as corporate identity in this leaflet are trademarks of Lonking Holdings Ltd., and may not be used without written permission.

Specifications and design are subject to change without prior notice. Machines shown may not include optional accessories.

LONKING (FU JIAN) INTERNATIONAL TRADE CO.,LTD.
LONKING HOLDINGS LIMITED
 Add:26 Minyi Road,Xinqiao,Songjiang Industrial Zone,Shanghai
 Tel: +86-21-3760 2242 E-mail:export@lonking.cn
<http://www.lonkinggroup.com>

- OPERATING WEIGHT:
 21100kg
- ENGINE POWER:
 129kW
- BUCKET CAPACITY:
 0.9m³
- TRAVEL SPEED:
 3.2/5.1km/h